



Subminiature Rotary Coded Switches

Specifications:

Contact rating:	24 V DC, 25 mA switching
Contact resistance:	< 100 mΩ
Insulation resistance:	> 1000 MΩ
Dielectric strength:	250 V, 50 Hz for the duration of 1 minute
Operating temperature:	- 25° to + 70° C
Mechanical life:	minimum 2000 operations
Terminals:	phosphor bronze, gold-plated over nickel barrier
Material:	case: PBT blue, meets UL 94 V-0, washable, rotor: white; inverse type red
Mounting:	on pc-board
Soldering conditions:	auto-soldering – max.: 5 sec, 260° C

Models: Code

DRS 20010	BCD			
DRS 20110	BCD Inverse			
DRS 20016	Hexadecimal			
DRS 20116	Hexadecimal Inverse			
DRS 21010	BCD			
DRS 21110	BCD Inverse			
DRS 21016	Hexadecimal			
DRS 21116	Hexadecimal Inverse			
DRR 20010	BCD			
DRR 20110	BCD Inverse			
DRR 20016	Hexadecimal			
DRR 20116	Hexadecimal Inverse			
DRR 21010	BCD			
DRR 21110	BCD Inverse			
DRR 21016	Hexadecimal			
DRR 21116	Hexadecimal Inverse			

Special version:

