Metal Keyboard Inquiry Form

Company	
Department	
Attention	
Address	
	Postcode
Phone	Fax
Email	Web
Requir	rements
Short description of the application: Switching technology (for modifications please identify the basic standard product in brackets):	Touchscreen/Display integration (for control panels): ☐ Resistive Touchscreen with inch ☐ capacitive Touchscreen with inch ☐ Display area with inch
☐ YME IP☐ YME SF☐ YME MF☐ (Touch)Panel (with or without switches) Construction, mounting type anddimensions:	Marking type:☐ Laser marking☐ Chemische engraving (with colour selection)
 □ Front plate*: Dimensions: mm long, mm wide □ Front panel version □ Rear mount version □ Others (attachment) □ Display-/touchscreen-cut-out for control panels (attachment) 	□ back lite (with colour selection) Legending: □ Standard layout in (Country layout) □ Short description
 ☐ Housing: Dimensions: mm long, mm wide, mm deep (Please attach extra description) Required protection level: ☐ IP65 ☐ IP68 ☐ IP69k 	Additional input components: ☐ Trackball with mm diametre ☐ stainless steel trackball ☐ Resin trackball ☐ Touchpad ☐ Special switches and keys (attachment)
Surface: Untreated Brushed High gloss Others: Number, shape and position of the keys:	Interface: ☐ Matrix with PIN connector ☐ Standard edge, male strip, 12 pins, 2.54 mm ☐ Others
Keys (number) Round with diametre	☐ USB ☐ PS/2 ☐ RS232
☐ Elliptic with diametre☐ Rounded squared with length☐ Squared with length	Background informations: Expected quantity:
☐ Others (please add attachment)	Receiving of drawing and offer: (date)
* For rear mount versions only the "visiblearea" (without mounting border) has to be specified	Demanded date for receiving the first delivery: (date)