


toggle shown in pos. 1

P.C. MOUNTING



CONTACT ARRANGEMENT

code for x	function	toggle in pos. 1	toggle opposite to pos. 1
N	On-On	2-3, 5-6	1-2, 4-5
R	On-Mom		

code for x	function	toggle in pos. 1	toggle in center	toggle opposite to pos. 1
P	On-Off-On	2-3, 5-6	open	1-2, 4-5
S	Mom-Off-Mom			
T	On-Off-Mom			
PA	On-On-On	2-3, 5-6	2-3, 4-5	1-2, 4-5

RATING AND CONTACT/TERMINAL SURFACE

y	contacts	terminals	rating
Q	Ag over Ni	Ag over Ni	28 VDC / 3 A 125 VAC / 3 A 250 VAC / 1 A
empty	Au over Ni	Au over Ni	0.4 VA, max. 20 V AC/DC
G	Au over Ag over Ni	Au over Ag over Ni	28 VDC / 3 A 125 VAC / 3 A 250 VAC / 1 A
T	Au over Ag over Ni	Sn	28 VDC / 3 A 125 VAC / 3 A 250 VAC / 1 A
X	Au over Ni	Sn	0.4 VA, max. 20 V AC/DC

Compliance: RohS II (2011/65/EU)

Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	<h1>TST 2 x y RA</h1>
		03/05	dr	
Contact arrangement	10/14	dr		<h2>30 05 90</h2>
Rename	10/13	dr		
Revised	06/13	dr	knitter-switch	Page
IP rating	04/12	dr		1/2
Modifications	Date	Name		

Specifications:

Contact resistance: 20mOhm max. at 2-4V DC
Insulation resistance: 1 000MOhm min.
Dielectric strength: 1 000V RMS
Operating temperature: -30°C to +85°C
Mechanical life: 50 000 make-and-break cycles
Material: Case and bushing: glass filled nylon 6/6, flame retardant,
 heat stabilized (UL94V-0)
 Actuator: brass, chrome plated
 Switch support: brass, tin plated
 Terminals / contact: copper
 IP rating: IP67

Compliance: RohS II (2011/65/EU)

Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	TST 2 x y RA
		03/05	dr	
			knitter-switch	30 05 90
				Page
				2/2
Modifications	Date	Name		